

UL 600V 18AWG 16AWG TFFN TFN





www.himakecable.com
info@himakecable.com

電壓 600V
符合 ASTM-B3 及 ASTM-B174 標準
線徑 18AWG 16AWG
絕緣材料 PVC
符合 UL62
溫度 90°C
UL62

規格

TFFN 及 TFN 符合 NEC 標準 90°C 60°C AWM 105°C 600V

規格 請洽 info@himakecable.com

TFFN Copper Conductor

Size (AWG) and Number of Conductors	No. of Strands	PVC Insulation Thickness (Conductor)		Nylon Jacket Thickness		Outside Diameter		Approximate Net Weight		Allowable Ampacity (Amps) ¹
		(mm)	(in)	(mm)	(in)	(mm)	(in)	(kg/km)	(lbs/1000ft)	
18	16	0.380	0.015	0.100	0.004	2.24	0.088	12	8	6
16	26	0.380	0.015	0.100	0.004	2.57	0.101	16	11	8

TFN Copper Conductor

Size (AWG) and Number of Conductors	No. of Strands	PVC Insulation Thickness (Conductor)		Nylon Jacket Thickness		Outside Diameter		Approximate Net Weight		Allowable Ampacity (Amps) ¹
		(mm)	(in)	(mm)	(in)	(mm)	(in)	(kg/km)	(lbs/1000ft)	
18	Solid	0.380	0.015	0.100	0.004	1.99	0.0783	12	8	6
16	Solid	0.380	0.015	0.100	0.004	2.26	0.0888	16	11	8

¹ Allowable ampacity shown above is per the National Electrical Code, Table 402.5. The above data is approximate and subject to normal manufacturing tolerances. The above data is approximate and subject to normal manufacturing tolerances.



1.







3. 10 60 international



