



000000 600V

000 18~14AWG 000

000 00

000 0000 + 00

000000 Black-Brown-Red-Orange-Yellow-Green-Blue-Violet-Grey-White-Transparent-Green/Yellow,etc

000000000 ± 0.10 m m

000 305 0000 200 0 00000000

00000 -60 °C 0 + 200 °C

UL3071/3074

UL3071/3074

UL3071/3074 符合 UL758 & UL 1581 及 RoHS 标准

UL3071/3074

UL3071/3074 符合 UL758 & UL 1581 及 RoHS 标准

UL3071/3074 (info@himakecable.com):

UL3071/3074	UL3071/3074	UL3071/3074	UL3071/3074	UL3071/3074	UL3071/3074 20 °C	UL3071/3074 20 °C-AMR
UL3071	18	7 × 0.39	0.96	3.11	22.2	11.01
UL3071	16	7 × 0.50	0.96	3.45	14.0	17.52
UL3071	14	41 × 0.26	0.96	3.75	8.78	27.84
UL3074	12	45 × 0.32	0.96	4.40	5.31	88.40

UL3071/3074

1. UL3071/3074 符合 UL758 & UL 1581 及 RoHS 标准



2. 在下列各题中，选择正确的答案。

1. 1



□□□□□□



3. 10 60





00 00000000 000000000000"0000".