



00000 600V

000 1814AWG000

000 000

000 0000+00

00000 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 00 - 00/000

000000 ±0.100

000 AWM 3071

000 00305002000 00000000

Temperature -60°C + 200°C

UL3071 / 3074

UL758& UL 1581, RoHs

info@himakecable.com

|        | AWG | mm      | mm   | mm   | 20°C | 20°C-AMR |
|--------|-----|---------|------|------|------|----------|
| UL3071 | 18  | 7×0.39  | 0.96 | 3.11 | 22.2 | 11.01    |
| UL3071 | 16  | 7×0.50  | 0.96 | 3.45 | 14.0 | 17.52    |
| UL3071 | 14  | 41×0.26 | 0.96 | 3.75 | 8.78 | 27.84    |
| UL3074 | 12  | 45×0.32 | 0.96 | 4.40 | 5.31 | 88.40    |

1.



□ □ □ □ □ □    □ □ □ □ □ □    □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□□□□



□□□□□□





[illegible]



00000000 0000000000000000000000000000 000000000000000000



