

海迈电缆
Himake Cable



www.himakecable.com
info@himakecable.com

导体 CCS + CCA / CCA / CCU / BC

导体直径 0.50mm 24AWG 25AWG 26AWG

长度 2 100

绝缘 PE HDPE

符合 4 类标准 / - ; / - ; / - ; / - 符合 ANSI / TIA / EIA-568-B

符合 PVC 符合 RoHS 符合 LSZH

符合 符合

符合 100 200 符合 305

符合 UTP Cat3 HSYV-3 HSYZ-3

IEC / ISO11801 IEC61156-2 ANSI / EIA / TIA 568 B.2 UL444 YD / T1019

RoHS

RoHS; NEXT/FEXT; CCS + CCA / CCA / CCU / BC HDP / PE FRPVC / LSOH PVC

Performance

Cat3 LAN 10Base-T 100Base-T4 100VG-AnyLAN

info@himakecable.com

mm	No./mm	mm	mm	mm	Kg / km
1x2x0.5	1 / 0.5	0.22	0.6	3.4	14
2x2x0.5	1 / 0.5	0.22	0.6	4.2	26
3x2x0.5	1 / 0.5	0.22	0.6	4.8	29.7
4x2x0.5	1 / 0.5	0.22	0.6	5.5	37.5
8x2x0.5	1 / 0.5	0.22	0.7	7	58

CCA/CCS

1. CCA/CCS



2. □□□□□□ □□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□



3. 10 60

海迈电缆
Himake Cable



www.himakecable.com
info@himakecable.com





4. 圖 4-1 鋼 絲 繩 的 倉 庫 存 儲 與 裝 卸 流 程 示 意 圖



