

海迈电缆
Himake Cable



www.himakecable.com
info@himakecable.com

□□□□□ 1000V

□□□ □□□□□□□□

□□□□□ 18 ~ 10AWG

□□□ □□□□□

□□□□□□□□ □□□ □□□ □□□ □□□ □□□□□□□□□□

□□□ □□□□□

□□□□□ □□□□□□□□□□□□□□

□□□ 100 □□□□□□□ □□□□□

Operating temperature range: 90 °C to -40 °C

Complies with UL2277 and UL1277

UL

Features

High performance, low loss, low smoke, low halogen

Applications

Industrial applications

Contact us at info@himakecable.com

Cable Type	Dimensions	Weight (kg/100m)	Volume (cm³/100m)	Approx. Length (m)
WTTC 2 × 18AGW	41V0.16	0.76	1.14	8.1
WTTC 3 × 18AGW	41V0.16	0.76	1.14	8.5
WTTC 4 × 18AGW	41V0.16	0.76	1.14	9.2
WTTC 2 × 16AGW	65V0.16	0.76	1.14	8.7
WTTC 3 × 14AGW	41V0.254	0.76	1.14	10.0
WTTC 4 × 12AGW	65V0.254	0.76	1.14	12.1
WTTC 5 × 10AGW	65V0.32	0.76	1.52	15.9

Notes

1. Cable length is subject to change without notice.
2. Cable weight and volume are approximate values.
3. Cable length is approximately 60 meters per 1000 grams.
4. Cable length is subject to change without notice.
5. Cable weight and volume are approximate values.