

□□□□



□□□□ 0.6/1 K V

□□□ 2 □□□□□□□□□□

□□□□□□□□ 1.5 ~ 300sqmm

□□□ 2 C ~ 4 C + E

□□□ XLPE

□□□□□□ 2 C + E: □□ + □□ + □/□□□3 C + E □□ + □□ + □□ + □/□□□4 C + E □ + □ + □ + □□ + □/□□

□□□ 5V-90 PVC

□□□□□ □□□□□□□□

□□□□□□□ 90 °C

□□□ □□□□□□□□□□

□□□□□□□ XLPE □□□□

□□□□□ AS / NZS5000.1

□□□□

□□□□ □□□□□□□□□□□□□□ □□□□□□□□□□ RoHS □□□□□

□□□□

Copyright © 2000 by Himake Cable. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of Himake Cable.

聯繫我們 (如需索取資料請電 1352 8888 1000 或電郵 info@himakecable.com)

鋼絞線 規格 ²⁾	鋼絞線 規格	V-90鋼絞線 規格	5V 90鋼絞線 規格	鋼絞線重量 (kg/m ²)	鋼絞線 直徑	鋼絞線 鋼絲/股
2 × 1.5 + E	鋼絞線	0.7	1.8	1.5	8.4	106
2 × 2.5 + E	鋼絞線	0.7	1.8	2.5	9.8	159
2 × 4.0 + E	鋼絞線	0.8	1.8	2.5	11.4	20.8
2 × 6.0 + E	鋼絞線	0.8	1.8	2.5	12.4	257
2 × 10 + E	鋼絞線	0.8	1.8	4.0	16.1	435
2 × 16 + E	鋼絞線	0.8	1.8	6.0	18.0	597

備註

1. 鋼絞線 規格以鋼絞線規格為準





□□□□□□



3. 10mm 60mm





4. 000000 0000 0 00000 00000000000 000000000000000000000000



5. □□□□□□ □□□□□□□□□□□□□□□□□□□□□□ □□□□□ □□□□□□□□□□□□□□□□



□□□□□□

□□ □□□□□□ □□ □□□□□□□□□□"□□□□".