



Produkteigenschaften

1. hohe Festigkeitsträger Kevlar Garn
2. mehr eng gepufferten design
3. Runde Konstruktion, weich, leicht, Streifen
4. 2 ~ 48 Kerne
5. Außenmantel Material: PVC, PU, OFNP, LSZH

Produktanwendung

Angenommen, indoor Verteilung, geeignet für Bodenanschluss, geeignet für Kommunikationsgeräte.

Produkt-parameter (weitere Informationen mailen Sie uns: info@himakecable.com)

Kabel Kern	Äußeren Ø	Gewicht	Min. zulässigen Zugfestigkeit (N)		Min. zulässige Last zerdrücken (N / 100mm)		Min. Biegeradius (mm)	
			Kurze Begriff	Lange Begriff	Kurze Begriff	Lange Begriff	Kurze Begriff	Lange Begriff
02	3.0	15	600	200	1000	200	20D	10D
04	4.0	22	600	200	1000	200	20D	10D
06	4.0	23	600	200	1000	200	20D	10D
08	5.0	27	600	200	1000	200	20D	10D
10	5.0	30	600	200	1000	200	20D	10D
12	6.0	35	600	200	1000	200	20D	10D
24	8.3	46	600	200	1000	200	20D	10D

Produktvorteile

(1) der Leiter ist aus hochwertigen optischen Fasern, es hat geringe Dispersion und Dämpfung, gewährleisten eine sehr gute Signale und Daten-Übertragung-Fähigkeit.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.