Produkteigenschaften

1. nehmen Sie Glasfaser-Band als Zentrum, Einheit Aramid Garn Festigkeitsträger rund um
2. Flexible, leicht abziehen, kleinen Biegeradius
3. 2 ~ 12 Kerne
4. Außenmantel Material: PVC, LSZH, OFNP

Produktanwendung

Indoor Verteilung angenommen. Geeignet für Patchkabel und Zöpfen, Anwendung für die Zusammenschaltung zwischen Geräten.

Produkt-parameter (weitere Informationen mailen Sie uns: info@himakecable.com)

Kabel Kern	Äußeren Ø	Gewicht	Min. zulässigen Zugfestigkeit (N)		Min. zulässige Last zerdrücken (N \/ 100mm)		Min. Biegeradius (mm)	
Graf	(mm)	(kg\/km)	Kurze Begriff	Lange Begriff	Kurze Begriff	Lange Begriff	Kurze Begriff	Lange Begriff
02	3.5x2.5	13	500	100	500	100	20D	10D
04	3.5x2.5	13	500	100	500	100	20D	10D
06	4.2X2.5	15	500	100	500	100	20D	10D
08	4.5x2.2	15	500	100	500	100	20D	10D
12	4.8x2.2	17	500	100	500	100	20D	10D

Produktvorteile

(1) der Leiter ist aus hochwertigen optischen Fasern, es hat geringe Dispersion und Dämpfung, gewährleisten eine sehr gute Signale und Daten-Übertragung-Fähigkeit.

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com