Product Description:
Conductor: Bare Copper
Conductor size: 0.32mm, 0.4mm, 0.5mm, 0.6mm, 0.7mm, 0.9mm
Insulation: HDPE
Cores: 5~2400 pairs, 100 pair and above has the 1% prepared line pairs that is not more than 6 pairs
Insulation color: there is 10 kinds color in total, every pair's insulation color is according to stated chromatogram
Wrapping tape: polyester tape
Shield: Aluminum band, both sides of the aluminum band combine the polyolefin membranes with thickness 0.05mm
Self-support wire: steel wire
Sheath: LDPE
Sheath color: black, or other as per requirement
Package: 100 meters per roll, 500 meters per wooden reel, wooden drum or as per requirement
Main product model: HYA
Product standard: GY/T 322, IEC 708-1, PEA PE-22

Product application:
It is aerial communication cable, applicable to the transmission of analogue signal with audio frequency 150KHZ or less, and the transmission of digital signal of 2048Kbits/s or less, also the digital signal of above

2048Kbits/s in special condition.

Product Electrical Property: (more spec. details please email us: info@himakecable.com)

Cores & Conductor size (mm)	Approx. OD of main cable (mm)	Approx. OD of secondary cable (mm)	Approx. cable weight (kg/km)
10×2×0.40	21	9	335
15×2×0.40	22	10	342
20×2×0.40	23	10	357
25×2×0.40	23	11	382
30×2×0.40	24	12	402
50×2×0.40	25	14	461
100×2×0.40	30	18	640
150×2×0.40	33	21	848
200×2×0.40	36	24	1012



mm/inch
ZERO
mm
info@himakecable.com