Características del producto

1. miembro de hilado de kevlar de alta resistencia
2. más apretado con diseño
3. redondo de construcción, suave, fácil para
4. 2 ~ 48 corazones
5. exterior de la envoltura material: PVC, LSZH, OFNP, PU

Aplicación de productos

Adoptada para la distribución interior, adecuado para la conexión de la planta, conveniente para el equipo de comunicación.

Parámetro del producto (más detalles por favor, envíenos un correo: info@himakecable.com)

Cable núcleo	Exterior Diámetro	Peso	Min. resistencia a la tracción admisible (N)		Min. Carga admisible de aplastar (N \/ 100mm)		Min. Radio de curvatura (mm)	
Conde	(mm)	(kg\/km)	Corto plazo	Largo plazo	Corto plazo	Largo plazo	Corto plazo	Largo plazo
02	3.0	15	600	200	1000	200	20D	10D
04	4.0	22	600	200	1000	200	20D	10D
06	4.0	23	600	200	1000	200	20D	10D
08	5.0	27	600	200	1000	200	20D	10D
10	5.0	30	600	200	1000	200	20D	10D
12	6.0	35	600	200	1000	200	20D	10D
24	8.3	46	600	200	1000	200	20D	10D

Ventajas del producto

1. el conductor se hace de fibras ópticas de alta calidad, cuenta con baja dispersión y atenuación, asegurando una muy buena capacidad de transmisión de señal y datos.

Brand new material

> Smooth

> Anti-UV

> Long-life

High Quality Fiber

> Fast

> Long and stability transmission

> Low Attenuation.

High Quality PBT Loose Tube Material

> Anti-aging

> Good Protection

info@himakecable.com

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com