



Características del producto

1. el diseño del cable Multi
2. Multi cada cable con el miembro de fuerza independiente
3. 2 ~ 144 corazones
4. miembro de fuerza central no metálicos de

Aplicación de productos

Adoptado para poner de interior nivel y vertical, colocación de techo, colocación superficial, etcetera. Conveniente para latiguillos y pigtails.

Parámetro del producto (más detalles por favor, envíenos un correo: info@himakecable.com)

Cable núcleo	Exterior Diámetro	Peso	Min. resistencia a la tracción admisible (N)		Min. Carga admisible de aplastar (N V 100mm)		Min. Radio de curvatura (mm)	
			Corto plazo	Largo plazo	Corto plazo	Largo plazo	Corto plazo	Largo plazo
Conde	(mm)	(kg/km)						
12	15.5	205	1500	500	1500	600	20D	10D
24	15.5	205	1500	500	1500	600	20D	10D
36	17.5	255	1500	500	1500	600	20D	10D
48	17.5	255	1500	500	1500	600	20D	10D
60	19.5	320	1500	500	1500	600	20D	10D
72	19.5	320	1500	500	1500	600	20D	10D
96	22	395	1500	500	1500	600	20D	10D
144	28	597	1500	500	1500	600	20D	10D

Ventajas del producto

1. el conductor se hace de fibras ópticas de alta calidad, cuenta con baja dispersión y atenuación, asegurando una muy buena capacidad de transmisión de señal y datos.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.