



www.himakecable.com
info@himakecable.com

Caratteristiche del prodotto

1. alta resistenza kevlar filati membro
2. più stretto tamponata design
3. costruzione, morbida, rotonda facile a striscia
4. 2 ~ 48 core
5. Materiale guaina esterna: PVC, LSZH, OFNP, PU

Applicazione del prodotto

Adottato alla distribuzione interna, adatto per collegamento a pavimento, adatto per apparecchiature di comunicazione.

Parametro del prodotto (maggiori dettagli si prega di contattarci via email:

Cavo Core conteggio	Esterno Dia. (mm)	Peso (kg/km)	Min. resistenza alla trazione ammissibile (N)		Min. Carico ammesso di schiacciamento (N/100mm)		Min. Raggio di curvatura (mm)	
			Breve termine	Lungo termine	Breve termine	Lungo termine	Breve termine	Lungo termine
02	3.0	15	600	200	1000	200	20D	10D
04	4.0	22	600	200	1000	200	20D	10D
06	4.0	23	600	200	1000	200	20D	10D
08	5.0	27	600	200	1000	200	20D	10D
10	5.0	30	600	200	1000	200	20D	10D
12	6.0	35	600	200	1000	200	20D	10D
24	8.3	46	600	200	1000	200	20D	10D

Vantaggi del prodotto

1. il conduttore è fatto di fibre ottiche di alta qualità, ha bassa dispersione e attenuazione, garantendo una molto buona capacità di trasmissione di segnali e dati.



Brand new material

- > **Smooth**
- > **Anti-UV**
- > **Long-life**

High Quality Fiber

- > **Fast**
- > **Long and stability transmission**
- > **Low Attenuation.**



High Quality PBT Loose Tube Material

- > **Anti-aging**
- > **Good Protection**

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.