



- Rip Cord
- Optical fiber
- Loose tube
- FRP
- Water blocking tape
- Inner PE sheath
- Aramid yarns
- Outer HDPE sheath
- Filler



www.himakecable.com  
info@himakecable.com

ADSS 光纤直径为250um 采用FRP (玻璃纤维) 增强，PE 护套，AT (芳纶) 纤维，符合 IEEE 1222-2004, IEC60794-1

- 2 ~ 144 芯
- 25 kv 电压等级
- 1500 米 backprops
- 90KN 抗拉强度
- 工作温度: -40 ~ + 70 度

## 製品仕様書

製品名: 光ファイバーケーブル

製品番号: LAN-001

お問い合わせ先 (Eメール: [info@himakecable.com](mailto:info@himakecable.com))

ケーブル径 (mm)	ケーブル長さ (m)	引張強さ (N/mm <sup>2</sup> )	曲率半径 (1/k)	重量 (Kg/km)	引張力 (N)	
仕様: 35 m/s 0 mm						
24	15.5	800	$2.86 \times 10^2$	$0.02 \times 10^2$	200	29680
仕様: 10 m/s 5 mm						
24	14.5	800	$2.33 \times 10^2$	$0.11 \times 10^2$	185	19600

## 注意事項

- 本製品は、直射日光や高温多湿の環境に長時間さらされず、取り扱いに注意してください。



**Brand new material**

- > Smooth
- > Anti-UV
- > Long-life

**High Quality Fiber**

- > Fast
- > Long and stability transmission
- > Low Attenuation.



**High Quality PBT Loose Tube Material**

- > Anti-aging
- > Good Protection

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



## APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

### Packaging & Shipping

## PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.