製品の説明

海迈电缆
Himake Cable
钢丝绞线 Stranded wires
聚乙烯护套 PE sheath
光纤 Fiber
套管填充物 Tuber filling compound
松套管 Loose tube
缆芯填充物 Cable filling compound
涂塑钢带 PSP
聚乙烯护套 PE sheath
中心加强芯 Central strength member
CE
SAA
UL
CB
RoHS
www.himakecable.com
info@himakecable.com

繊維、250um は、高弾性のプラスチック製のルース チューブに配置されます。チューブは、耐水性充填化合物で満ちています。鋼線をコアの中心部に金属の強度メンバーとして検索します。コンパクトで円形コア強度メンバー周辺管 (とフィラー) の撚り線が。チューブは、PSP とルーズ チューブの間縦、PSP の層でラップされ、コンパクトで防水ケーブルを保つために水ブロック マテリアルが適用されます。チューブ周り PSP を適用した後、ケーブルの撚り線ケーブルに伴う支援の一環としてのこの部分は PE シースは、図 8 の構造と完成品します。
標準: ヤード/T 1155-2001 年 IEC60794-1

製品の特性

1. 2 ~ 228 繊維、ゼリーいっぱい含まれる繊維ルース チューブ
2. 良い環境性能
3. 耐加水分解性、高強度ルース チューブ
4. 特殊チューブ充填複合繊維の重要な保護を確保します。
5. ステンレス鋼または自己サポート メンバーとして亜鉛めっき鋼メッセン ジャー ワイヤ反引っ張り性能に優れ、簡単にインストールを行います。
6. 良いケーブル防水。
7. ストレージ/動作温度範囲:--40 ~ + 70

製品アプリケーション

レイアウト モード: エアリアル・コンジット
屋外配電を採用
長距離およびローカル エリア ネットワーク通信

製品パラメーター (詳細については、してください電子メール私達: info@himakecable.com)

繊維カウント	鋼メッセンジャー	ケーブル質量	最小曲げ半径 (mm)		張力 (N)		Max。荷重をつぶす (N/1000 mm)	
コア	(mm)	(Kg/km)	静的な状態	動的な状態	Max。	安全な緊張	短期的には	長期的
2-24	7/3.0	190	10 D	30%	4950	2500	2000	1000
26-36	7/3.0	200	10 D	30%	4950	2500	2000	1000
38-60	7/3.0	235	10 D	30%	4950	2500	2000	1000
2-24	7/3.6	200	10 D	30%	7100	3500	2000	1000

製品の利点

1. 導体は最高品質の光ファイバー、低分散、減衰、非常に良い信号およびデータ伝送能力を確保しています。

Brand new material

> **Smooth**

> **Anti-UV**

> **Long-life**

High Quality Fiber

> **Fast**

> **Long and stability transmission**

> **Low Attenuation.**

High Quality PBT Loose Tube Material

> **Anti-aging**

> **Good Protection**

info@himakecable.com

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com