



250um 光缆...
 ...PE ...
 标准: GB/T 769-2003 IEC60794-1

1. 2 ~ 24 芯
2. ...
3. ...
4. ...
5. ...
6. ...
7. 工作温度: -40 ~ + 70℃

株式会社 三和電線
 三和電線 LAN 製品部

お問い合わせ先 (お問い合わせ先: info@himakecable.com)

Fコード コード	外径 (mm)	重量 (Kg/km)	外径 (mm)		引張力 (N)		Max引張力 (N/1000 mm)	
			外径	外径	引張力	引張力	引張力	引張力
2-6	8.9	116	10 D	30%	1500	600	1000	300
6-12	10.9	132	10 D	30%	1500	600	1000	300

三和電線

- 三和電線株式会社



Brand new material

- > **Smooth**
- > **Anti-UV**
- > **Long-life**

High Quality Fiber

- > **Fast**
- > **Long and stability transmission**
- > **Low Attenuation.**



High Quality PBT Loose Tube Material

- > **Anti-aging**
- > **Good Protection**

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.