

□□: □□□/T 1155-2001 □ IEC60794-1

- 1. 2 ~ 24 000000000 0000
- 2. 00000000
- 3. חחחחחחחחחחחח חחחח

- 6. Decided by the second of th

0000 000: 00

$\square\square\square\square\square\square\square\square$ ($\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square$: info@himakecable.com)

			□□□□□ (mm)		□□ (N)		Max[[[[[[[[[[
							(N/1000 mm)	
	(mm)	(Kg/km)			Max[]			
2-12	7/3.0	135	10 D	30%	3000	1000	2000	1000



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- Long and stability transmission
- > Low Attenuation.





High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.









Optic Fiber Cable Testing

- · Fiber Testing
- · Testing after fiber coloring
- · Testing after fiber stranding
- · Testing after fiber optic cable jacketing



APPLICATION







Pipeline

Overhead

✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



 Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.