□□□□□

□□□250um □□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□ PE □□□□□□□□□□□□□ □□ (□□□□□□) □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□ □□□□□□□□□ (APL) □□□□□□□□□□□□□□□□□□□□□□ PE □□□□□□□□□□□□□□□□□□ □□□□ PSP □□□□□PE □□□□□□□□□□□□ □□

□□: □□□/T 901-2001□IEC60794-1

□□□□□

1. 2 □ 228 □□□□□□□□□□□□□□□□□□□□□ □□□□
2. □□□□□□□□□
3. □□□□□□□□□□□□□ □□□□
4. □□□□□□□□□□□□□□□□□□□□□□□□□□
5. □□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□
6. □□□□□□□□
7 PE □□□ □□□□□□□□□□□□□□□□□
8. □□□□□□□□□

[illegible]

[illegible] [illegible]: [illegible] & [illegible]
[illegible]
[illegible] [illegible] [illegible]

[illegible] ([illegible]: info@himakecable.com)

[illegible] [illegible]	[illegible] φ	[illegible]	[illegible] (mm)		[illegible] (N)		Max[illegible] (N/1000 mm)	
[illegible]	(mm)	(Kg/km)	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
2-24	13.3	210	12.5 D	35%	3000	1000	3000	1000
26-36	13.6	220	12.5 D	35%	3000	1000	3000	1000
38-60	14.1	225	12.5 D	35%	3000	1000	3000	1000
62-72	14.6	255	12.5 D	35%	3000	1000	3000	1000
74-96	16.2	305	12.5 D	35%	3000	1000	3000	1000

[illegible]

1. [illegible]

Brand new material

> Smooth

> Anti-UV

> Long-life

High Quality Fiber

> Fast

> Long and stability transmission

> Low Attenuation.

High Quality PBT Loose Tube Material

> Anti-aging

> Good Protection

info@himakecable.com

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com