



3 銅絞線 CCA 銅絞線電纜電纜

電壓: 300/500V 450/750V

電纜 銅絞線電纜電纜電纜CCA

電纜電纜: 0.75 16mm

電纜: 2C 2CE

電纜 PVC 電纜 PVC PE LSZH LSHF

電纜電纜: 2C: 電纜電纜3C: 電纜電纜2CE: 電纜電纜 E 電纜電纜電纜電纜

電纜 PVC 電纜 PVC LSZH LSHF

電纜電纜: 電纜電纜電纜電纜電纜

電纜電纜電纜: 70°C 90°C

電纜電纜 電纜電纜 100 電纜電纜電纜電纜電纜

電纜電纜電纜: BVVB H05VVH2-U H07VVH2-R BS6004 624*Y

電纜電纜 IEC60277 BS6004 VDE0281 GB/T 5023

重要事項:

本製品はRoHS指令に適合しています。

重要事項:

本製品はRoHS指令に適合しています。本製品のRoHS適合性は、本製品のRoHS適合性を保証するものではありません。本製品のRoHS適合性は、本製品のRoHS適合性を保証するものではありません。

お問い合わせ先: (お問い合わせ先)info@himake.com

品名 (単位)	数量	材質	仕様	寸法	重量
2×1.0	1	PVC/0.6	PVC/0.9	4.8×7.4	46
2×1.5	1	PVC/0.7	PVC/0.9	5.3×8.3	64
2×1.5	2	PVC/0.7	PVC/0.9	5.4×8.4	71
2×2.5	2	PVC/0.8	PVC/1.0	6.2×10.1	97
2×1.01.0(E)	1	PVC/0.6	PVC/0.9	4.7×8.6	68
2×1.51.0(E)	2	PVC/0.7	PVC/0.9	5.4×9.6	87
2×2.51.5(E)	2	PVC/0.8	PVC/1.0	6.2×11.5	120
2×4.01.5(E)	2	PVC/0.8	PVC/1.0	7.2×13.0	170
2×6.02.5(E)	2	PVC/0.8	PVC/1.1	8.0×15.0	240

重要事項:

ADVANTAGE

WHY US?

Source manufacturers direct, non - agent, no price difference



Professional instrument detection,
strict control, adhere to the quality .



Swing test



Tensile strength test



Print friction test



Temperature test



Insulation resistance test



UV test

PACKAGING LOGISTICS

[illegible]

