

□□□□:



□□□□: 0.6/1 KV

□□: □□ 1 □□□□□□□□ 2 □□□□□□□□□□□□

□□□□□□: 1.5 □ 800sqmm

□□□: □□□□□□□□

□□□□□: 2 C: □ + □□3 C: □ + □ + □□ 4 C: □ + □□ + □ + □□5 C: □ + □□ + □ + □ + □□□□ □□□□□□□□□□□□□□3 + 1 C□4 + 1 C□3 + 2 C

□: □□□□□□□□ PVC Rohs □□□□

□□□□□: □□□□□□□□□□

Max□□□□□□ 90

品牌: 希姆凯

型号: YJLVZR-YJLV U-1000 R2VRO2V

标准: IEC60502BS7889VDE0276IEC60332 GB/T12076

特性:

符合 RoHS 环保标准

技术参数:

适用于 ac 电压等级 U0/U 0.6/1 kv 及以下电压等级的固定敷设线路 (室内、室外、埋地、架空、水下等)

联系方式: (电子邮箱: info@himakecable.com)

导体截面积 (mm ²)	导体直径 (mm)	绝缘厚度 (mm)	PVC 护套厚度 (mm)	总外径 (mm)	重量 (Kg/Km)
1 × 1.5	1.4	0.7	1.4	5.6	52.4
1 × 2.5	1.8	0.7	1.4	6	65.4
1 × 4	2.2	0.7	1.4	6.4	83.1
1 × 6	2.8	0.7	1.4	7	106.7
1 × 10	4.1	0.7	1.4	8.3	157.7
1 × 16	5.1	0.7	1.4	9.3	221.6

备注:

1. 本产品为通用型电缆，具体规格请咨询销售。



□□□□□□



3. 10 60 internationally





