

□□□□:



□□□□: 300/500 V 450/750 V

□□: □□ 1 □□□□□□ 2 □□□□□□□□ □□□□□□□□

□□□□□□□□: 0.75~ 16sqmm

□□: 2 C□3 C□2 C + E□3 C + E

□□□: □□ PVC □□□□□

□□□□□□: 2 C: □□□□□□□□□□3 C: □□□□□□□□2 C + E: □□□□□□□□ E □□□□□□□□□□

□□: □□ PVC □□□□□

□□□□□□: □□□□□□□□□□□□□□

Max□□□□□□□□ 70□90

□□□□□□: 100 □□□□□□□□□□□□□□

□□□□□□□□: BVVB H05VVH2 U□H07VVH2 R□BS6004 624 * Y

□□□□□□: IEC60277□BS6004□VDE0281□GB/T 5023

□□□□:

RoHS Compliant

Table 1: Cable Specifications

Table 1: Cable Specifications

Contact: (Email: info@himakecable.com)

Cross Section (mm ²)	Number of Conductors	Conductor Insulation (mm)	Overall Insulation (mm)	Max Overall Diameter (mm)	Weight (KG/KM)
2 x 1.0	1	PVC/0.6	PVC/0.9	4.8 x 7.4	46
2 x 1.5	1	PVC/0.7	PVC/0.9	5.3 x 8.3	64
2 x 1.5	2	PVC/0.7	PVC/0.9	5.4 x 8.4	71
2 x 2.5	2	PVC/0.8	PVC/1.0	6.2 x 10.1	97
2x1.0+1.0(E)	1	PVC/0.6	PVC/0.9	4.7 x 8.6	68
2x1.5+1.0(E)	2	PVC/0.7	PVC/0.9	5.4 x 9.6	87
2x2.5+1.5(E)	2	PVC/0.8	PVC/1.0	6.2 x 11.5	120
2x4.0+1.5(E)	2	PVC/0.8	PVC/1.0	7.2 x 13.0	170
2x6.0+2.5(E)	2	PVC/0.8	PVC/1.1	8.0 x 15.0	240

Table 2: Cable Specifications

1. Cable Specifications





□□□□□□



3. 10 60 internationally





