



RE-2Y(St)CY

RE-2Y(St)CY

电压: 300/500V

符合 IEC60228 VDE0295 2类B类7类

导体规格: 0.5mm, 0.75mm, 1.0mm, 1.3mm, 1.5mm, 2.5mm

绝缘 PVC(Y); PE(2Y); XLPE(X)

结构: 12芯 b 芯 12芯 c 芯 Quadruplex: 4芯 b 芯 C 芯 D 芯

导体规格 0.5 sqmm (7/0.30 mm) PE 或 XLPE 绝缘 (符合 IEC60228)

电压: 300/500V

符合 IEC60228

导体规格: 0.5mm (7/0.3mm)

材料: 100% (St)C

材料: PVC

材料:

温度: -30~70°C: -5 ~ 50 °C

材料: 100

材料: RE-2Y(St)CY RE-Y(St)CY RE-2X(St)CY

材料: IEC60277 IEC60228 IEC60332-1 EN 50288-7

注意:

... () ...

注意:

...

联系: info@ himake

Table with 6 columns: Dimensions, Material, AWG-No., Diameter, Weight (kg/km), and another Weight (kg/km). Rows include various cable specifications like 2x2x0.5, 4x2x0.5, etc.

注意:

- 1. ...





□□□□□□



3. 15 international





□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□