海迈电缆
Himake Cable
Tight Buffer Fiber
Aramid Yarn
Subunit Jacket
Jacket
FRP Strength Member
www.himakecable.com
info@himakecable.com

□□□□□

(1) □□□ 1 □□□□□□□□
2 □□□□□□□□□□□□□□□□□□□□□□□□
3. 2 ~ 24 □□
4. □□□□□□□□□□□□

□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□

c□□□□□□□□	□□ Φ	□□	□□ □□□□□□ (N)		□□ □□□□□□□□□□ (N\/100 mm)		□□ □□□□ (mm)	
□□□□	(mm)	(kg\/km)	□□ □□	□□ □□	□□ □□	□□ □□	□□ □□	□□ □□
02	7.0	45	1500	500	1000	300	20 D	10 D
04	7.0	47	1500	500	1000	300	20 D	10 D
06	8.3	64	1500	500	1000	300	20 D	10 D
08	9.5	88	1500	500	1000	300	20 D	10 D
12	11.5	105	1500	500	1000	300	20 D	10 D
24	13.5	142	1500	500	1000	300	20 D	10 D

□□□□□

1. □□□□□□□□□□

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com