



Tight Buffer Fiber
Aramid Yarn
Subunit Jacket
Jacket
FRP Strength Member



www.himakecable.com
info@himakecable.com

产品特点

- (1) 符合 1 类标准
- 2 类标准
3. 2 ~ 24 芯
4. 符合标准

应用范围

广泛应用于各种通信网络、数据中心、工业控制等领域。

联系我们 (电子邮箱: info@himakecable.com)

Cable Type	Outer Diameter (mm)	Weight (kg/km)	Tensile Strength (N)		Bend Radius (NV100 mm)		Cable Length (mm)	
Model	(mm)	(kg/km)	Max	Min	Max	Min	Max	Min
02	7.0	45	1500	500	1000	300	20 D	10 D
04	7.0	47	1500	500	1000	300	20 D	10 D
06	8.3	64	1500	500	1000	300	20 D	10 D
08	9.5	88	1500	500	1000	300	20 D	10 D
12	11.5	105	1500	500	1000	300	20 D	10 D
24	13.5	142	1500	500	1000	300	20 D	10 D

Product Features

1. High quality fiber optic cable with excellent performance.



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.