



Infima PVC 300/500V H07V-K NYAF 450/750V

Infima: 300/500V 450/750V

Infima 5mm

Infima: 0.5 240mm

Infima PVC PVC RoHS PVC

Infima: 300/500V 450/750V / 450/750V

Infima: 70°C 90°C

Infima 100 300/500V

物料名称:RVZR-RVH05V-KH07V-KNYAF

执行标准 IEC60277BS6004VDE0281GB/T 5023IEC60332

规格:

本产品符合RoHS指令要求

性能:

额定电压 450/750V 额定电流

联系方式: (021) 60401000fo@himake.com

导体截面 (mm ²)	导体根数	绝缘材料	护套厚度 (mm)	重量 (kg/km)	绝缘电阻 (MΩ.km)
0.5	5	PVC/0.6	2.4	8.34	0.013
0.75	5	PVC/0.6	2.6	11.08	0.011
1	5	PVC/0.6	2.8	13.73	0.01
1.5	5	PVC/0.7	3.5	19.94	0.01
2.5	5	PVC/0.8	4.2	30.95	0.009
4	5	PVC/0.8	4.8	46.8	0.007
6	5	PVC/0.8	6.3	67.82	0.006

备注:

- 本产品符合RoHS指令要求



[illegible]



□□□□□□



3. 15 60 international





□□□□ □□□□□□□□ in □□□□□□ □□□□□□□□□□□□□□□□ □□□□□□□□□□□□ □□