



□□ □□ □□ □□□□□□ □□ □□□□ **ASNZS3013**

□□□□□ 450 / 750V

0.75 4.0

2C 4C 2C + E

2C 4C 2C + E

X-HF-110

2C; 4C; 2C + E

PET Al

HFS-110-TP

110°C

100/500

HF-110

AS / NZS 5000.2 AS / NZS 3013 - WS52W



Rohs



mm ²		mm		mm	O.D. mm
2x0.75	OFC	0.7	TC	1.2	9.5
2x1.5	OFC	0.7	TC	1.2	9.9
4x1.5	OFC	0.7	TC	1.2	11.7
2x0.75 + E	OFC	0.7	TC	1.2	9.8
2x1.5 + E	OFC	0.7	TC	1.2	10.2
4x1.5 + E	OFC	0.7	TC	1.8	13.0







□□□□□

Quality Comparison

Purity of copper



Excellent 99.93% Oxygen Free Copper ,
Bright color with long life time .



Inferior Copper including a lot of impurity
Easy heat, short life Easily cause fire

Flame Test



Excellent No spread , and release a little
white smoke



Inferior Keep burning , and pop a lot of black
HCL toxic smoke

Resistance Test



Excellent low resistivity, high conductivity



Inferior High resistivity, High consumption .
Easy to burning .

Eccentricity Ratio



Excellent Insulation thickness uniformity



Inferior Insulation thickness nonuniform
Easy electric leakage fire disaster,

High Pressure Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

High Temperature Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

Low Temperature Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

3. 10 60 international ly SAA





