



□□ □□ □□ □□□□□□ □□ □□□□ **ASNZS3013**

□□□□□ 450 / 750V

0.75 4.0

2C 4C 2C + E

X-HF-110

2C + ; 4C + + + ; 2C + E + +

PET + Al +

HFS-110-TP

110°C

100 / 500

HF-110

AS / NZS 5000.2 AS / NZS 3013 - WS52W

RoHS

info@himakecable.com

mm<sup>2</sup>

mm O.D. mm

info@himakecable.com

mm <sup>2</sup>		mm		mm	O.D. mm
2x0.75	OFC	0.7	TC	1.2	9.5
2x1.5	OFC	0.7	TC	1.2	9.9
4x1.5	OFC	0.7	TC	1.2	11.7
2x0.75 + E	OFC	0.7	TC	1.2	9.8
2x1.5 + E	OFC	0.7	TC	1.2	10.2
4x1.5 + E	OFC	0.7	TC	1.8	13.0

RoHS













□□□□□





## Quality Comparison

### Purity of copper



**Excellent** 99.93% Oxygen Free Copper ,  
Bright color with long life time .



**Inferior** Copper including a lot of impurity  
Easy heat, short life Easily cause fire

### Flame Test



**Excellent** No spread , and release a little  
white smoke



**Inferior** Keep burning , and pop a lot of black  
HCL toxic smoke

### Resistance Test



**Excellent** low resistivity, high conductivity



**Inferior** High resistivity, High consumption .  
Easy to burning .

### Eccentricity Ratio



**Excellent** Insulation thickness uniformity



**Inferior** Insulation thickness nonuniform  
Easy electric leakage fire disaster,

### High Pressure Test



**Excellent** Jacket no any damage



**Inferior** Jacket damaged , reveal conductor

### High Temperature Test



**Excellent** Jacket no any damage



**Inferior** Jacket damaged , reveal conductor

### Low Temperature Test



**Excellent** Jacket no any damage



**Inferior** Jacket damaged , reveal conductor

3. 10 60 international ly SAA















5. 5.12 汶川大地震 10 周年紀念活動 暨 社區服務活動



