

□□□□□□:



□□□□: 0.6/1 KV

□□: □□□□ □□□ 1 □□□□□□ 2 □□□□□□□□□□□□□□□□□□

□□□□□□□□: 1.5 □ 800sqmm

□□□: □□□□□□□□

□□□□□□: 2 C: □ + □□ 3 C: □ + □ + □□ 4 C: □ + □□ + □ + □□ 5 C: □ + □□ + □ + □ + □□□□ □□□□□□□□□□□□□□□□□ 3 + 1 C□4 + 1 C□3 + 2 C

□□: □□□□□□□□□□ PVC Rohs □□□□ PVC□PE□LSZH

□□□□□□: □□□□□□□□□□

Max□□□□□□□□ 90

□□□□□□: □□□□□□□□□□□□

Model: ZR-YJV YJV WDZ-YJY YJY U-1000 R2V RO2V

Standards: IEC60502 BS7889 VDE0276 IEC60332 GB/T12076

Features:

Low smoke, low halogen, flame retardant, meets RoHS requirements.

Applications:

Used for AC power cables with U0/U 0.6/1 kV, suitable for indoor and outdoor use.

Contact: info@himakecable.com

Cable Size (mm ²)	Conductor Diameter (mm)	Insulation Thickness (mm)	PVC Jacket Thickness (mm)	Overall Diameter (mm)	Weight (Kg/Km)
1 x 1.5	1.4	0.7	1.4	5.6	52.4
1 x 2.5	1.8	0.7	1.4	6	65.4
1 x 4	2.2	0.7	1.4	6.4	83.1
1 x 6	2.8	0.7	1.4	7	106.7
1 x 10	4.1	0.7	1.4	8.3	157.7
1 x 16	5.1	0.7	1.4	9.3	221.6

Notes:

1. All dimensions are in millimeters unless otherwise specified.



2 下列各句，没有语病的一句是（ ）

（ ）



□□□□□□



3. 10 60 internationally





4. 此項工作係由本廠之員工負責執行，所有之工作均須依照標準作業程序進行，以確保產品之品質與數量之準確。



