



[www.himakecable.com](http://www.himakecable.com)  
[info@himakecable.com](mailto:info@himakecable.com)

### 产品特点

1. 阻燃性能优异
2. 使用寿命长
3. 柔软性好，易于弯曲
4. 2 ~ 48 芯
5. 护套材料：LSZH / OFNP / PU

### 应用范围

广泛应用于工业、商业、民用等领域。

联系我们 (电子邮箱: [info@himakecable.com](mailto:info@himakecable.com))

Model	Core Diameter (mm)	Weight (kg/km)	Tensile Strength (N)		Bend Radius (NV100 mm)		Attenuation (mm)	
Model	(mm)	(kg/km)	600	200	1000	200	30%	10 D
02	3.0	15	600	200	1000	200	30%	10 D
04	4.0	22	600	200	1000	200	30%	10 D
06	4.0	23	600	200	1000	200	30%	10 D
08	5.0	27	600	200	1000	200	30%	10 D
10	5.0	30	600	200	1000	200	30%	10 D
12	6.0	35	600	200	1000	200	30%	10 D
24	8.3	46	600	200	1000	200	30%	10 D

**Product Features**

1. High Quality Fiber



**Brand new material**

- > Smooth
- > Anti-UV
- > Long-life

**High Quality Fiber**

- > Fast
- > Long and stability transmission
- > Low Attenuation.



**High Quality PBT Loose Tube Material**

- > Anti-aging
- > Good Protection

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.





## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



## APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

### Packaging & Shipping

## PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.