

- 4. 2 ~ 48 □□

5

	ПП Ф		00 00000 (N)		□□ □□□□□□□□ (NV100 mm)		00 0000 (mm)	
	(mm)	(kg\/km)				00 00		
02	3.0	15	600	200	1000	200	30%	10 D
04	4.0	22	600	200	1000	200	30%	10 D
06	4.0	23	600	200	1000	200	30%	10 D
08	5.0	27	600	200	1000	200	30%	10 D
10	5.0	30	600	200	1000	200	30%	10 D
12	6.0	35	600	200	1000	200	30%	10 D
24	8.3	46	600	200	1000	200	30%	10 D



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.





High Quality PBT Loose Tube Material

- > Anti-aging
- Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.









Optic Fiber Cable Testing

- · Fiber Testing
- · Testing after fiber coloring
- · Testing after fiber stranding
- · Testing after fiber optic cable jacketing



APPLICATION







Pipeline

Overhead

✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



 Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.