

规格: BVV BVVR H05VV H07VV H05VV-r H07VV BS6004

标准: IEC60277 BS6004 VDE0281 GB/T 5023 IEC60332

特性:

符合 RoHS 环保要求

应用:

适用于固定敷设的电力线路，如室内布线、室外布线、工业用电等。

联系我们: (邮箱: info@himakecable.com)

导体截面积 (mm ²)	绝缘厚度 (mm)	护套厚度 (mm)	总厚度 (mm)	电阻率 70°C (m ω • km)	重量 (kg/100m)
1×1.0	PVC/0.6	PVC/0.8	4.3	0.011	26
1×1.5	PVC/0.7	PVC/0.8	4.8	0.011	33
1×2.5	PVC/0.8	PVC/0.8	5.4	0.01	44
1×6.0	PVC/0.8	PVC/0.9	6.6	0.007	84
1×10	PVC/1.0	PVC/0.9	8.2	0.007	138
1×16	PVC/1.0	PVC/0.9	9.0	0.0050	204
1×25	PVC/1.2	PVC/1.0	11.7	0.0050	315
1×35	PVC/1.2	PVC/1.1	12.9	0.0040	415
1×50	PVC/1.4	PVC/1.3	15.2	0.0045	589
1×70	PVC/1.4	PVC/1.4	16.9	0.0035	790

备注:

1. 本产品符合 RoHS 环保要求





□□□□□□



3. 10 international 60







