



www.himakecable.com
info@himakecable.com

产品特点

1. 符合IEC60332-3-22标准
 2. 符合IEC60332-3-21标准
 3. 符合IEC60332-3-10标准
 4. 符合IEC60332-3-11标准
 5. 符合IEC60332-3-12标准
5. 符合IEC60332-3-12标准: LSZH/OFNP/PU

产品规格

符合IEC60332-3-22标准

产品规格 (如有需要, 请发送邮件至: info@himakecable.com)

| Item No. | Outer Diameter Φ (mm) | Weight (kg/km) | Max. Tensile Strength (N) | | Bend Radius (mm) | | Max. Pulling Force (N/mm ²) |
|----------|-----------------------------|-------------------|------------------------------|---------|---------------------|---------|--|
| | | | Static | Dynamic | Static | Dynamic | |
| 2 | 3.0 | 7.6 | 80 | 40 | 30% | 10 D | 500 |
| 2 | 5.0 | 19 | 160 | 80 | 30% | 10 D | 500 |

Advantages

1. High quality fiber and PBT loose tube material



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.