

□□□□:



□□□□: 300/500 V

□□: □□□□ □□□□□□□□ 5 □□□□□□

□□□: EPR □□

□□□□□: 2 C: □□□ + □□□3 C: □□□ + □□□□ + □/□□4 C: □□□□ + □□□□ + □□□ + □/□□ 5 C: □□□ + □□□□ + □□□ + □□□□ + □□□□/□□□□HD308/□□ 21089 1 □□□□

□: EPR □□

□□□□□: □□□□□□□□: □□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□

□□□□□: 100 m □□□□polywooden □□□□□□□□□□□□□□□□□□□□

Max□□□□□□ □□ 60

IEC VDE0282 BS 21027 4/HD 22.4

RoHS:

RoHS (Restriction of Hazardous Substances) PBBE (polybromium-biphenyls) CFC/HCFC (chlorofluoryhydrocarbons) RoHS 2002/95/EC

RoHS

RoHS:

H05RR F RoHS

RoHS: (Email: info@himakecable.com)

Core	Conductor		Insulation	Overall ϕ	Max. Conductor @ 20 ° c	
mm	mm ²	mm	mm	mm	Bare (Ω /km)	mm ² (Ω mm)
2	0.75	24/0.20	0.6	0.8	26.0	26.7
2	1.0	32/0.20	0.6	0.9	19.5	20.0
2	1.5	30/0.25	0.8	1.0	13.3	13.7
2	2.5	49/0.25	0.9	1.1	7.98	8.21
3	0.75	24/0.20	0.6	0.9	26.0	26.7

RoHS:

- RoHS



2 下列各题中，哪一个选项是正确的？

□□□□



□□□□□□



3. 10 60 internationally







