

[www.himakecable.com](http://www.himakecable.com)  
[info@himakecable.com](mailto:info@himakecable.com)

**产品特点**


1. 芯数 1 至 12 芯，FRP 增强，阻燃，低烟，无卤，符合 RoHS 标准。
2. 适用于 FTTH 网络。
3. 重量轻，易于安装。
4. 芯数 1 ~ 12 芯，可根据客户需求定制。
5. 符合 CE, UL, CB, CCC, SAA 等认证。
4. 符合 LSZH 阻燃标准。

**应用领域**

FTTH 网络、数据中心、工业环境等。

联系我们 (电子邮箱: [info@himakecable.com](mailto:info@himakecable.com))

外径 Φ (mm)	内径 Φ (um)	重量 (kg/km)	抗拉强度 (N)		弯曲半径 (NV100 mm)		最小弯曲半径 (mm)	
(mm)	(um)	(kg/km)	500	50	2000	1000	30%	10 D
2.1x3.1	250	8.5	500	50	2000	1000	30%	10 D
2.0x5.0	250	10.5	500	50	2000	1000	30%	10 D



1. 产品信息



**Brand new material**

- > Smooth
- > Anti-UV
- > Long-life

**High Quality Fiber**

- > Fast
- > Long and stability transmission
- > Low Attenuation.



**High Quality PBT Loose Tube Material**

- > Anti-aging
- > Good Protection

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.





## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



## APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

### Packaging & Shipping

## PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.