

□□□□□:



□□□□: 450/750v, 0.6/1kv

□□: □□□1□□□□□□□□□□□□2□□□□□□□□□□□□□□□5 □□□□□□□□□□□□□□□□

□□□□□□□□: 0.75 ~ 10sqmm

□□: pvc□□□□□ pvc□rohs □□ pvc

规格: 5芯 PVC 5芯 PVC 阻燃 PVC

规格: PVC 阻燃 PVC RoHS PVC

规格: 阻燃 PVC

规格: 70°C, 90 °C, 105 °C

规格: 阻燃 PVC 100% PVC 阻燃 PVC

规格: ZR-KVV ZR-KVVR

规格: IEC60277 BS6500 VDE0250 GB/T9330 IEC60332

规格:

规格: 阻燃 PVC 阻燃 PVC RoHS 阻燃 PVC

规格:

规格: 阻燃 PVC 阻燃 PVC 阻燃 PVC 阻燃 PVC 阻燃 PVC

规格 (450/750v):

(规格: info@himakecable.com)

规格 mm ²)	规格 mm)	规格 mm)	规格 mm)	规格 (规格)	规格 (ω/km) 20°C	规格 (m ω • km) 70°C
2x 0.75	pvc/0.6	pvc/1.2	7.5	67.72	24.5	0.012
2x 1.0	pvc/0.6	pvc/1.2	7.82	76.2	18.1	0.011
2x 1.5	pvc/0.7	pvc/1.2	8.74	97.71	12.1	0.011
2x 2.5	pvc/0.8	pvc/1.2	9.96	133.4	7.41	0.01
2x4	pvc/0.8	pvc/1.2	10.9	173.65	4.61	0.0085

规格:

1. 规格: 阻燃 PVC 阻燃 PVC 阻燃 PVC 阻燃 PVC 阻燃 PVC





□□□□□□



3. 10 60







5. 責任感 responsibility



