



www.himakecable.com  
info@himakecable.com

**产品简介**

1. 产品符合IEC60321-21-21标准
2. 产品符合IEC60321-21-21标准
3. 产品符合：LSZH/OFNP/PU

**产品特点**

产品符合IEC60321-21-21标准

产品符合IEC60321-21-21标准 (产品符合IEC60321-21-21标准: info@himakecable.com)

Φ	mm	(kgV/km)	(N)		(NV100 mm)		(mm)	
(mm)	(mm)	(kgV/km)						
3.0x5.0	1.8	56	800	300	1000	500	30%	10 D
3.2x5.6	2.0	68	800	300	1000	500	30%	10 D
4.0x7.2	2.8	87	800	300	1000	500	30%	10 D

( )

Φ	mm	(kgV/km)	(N)		(NV100 mm)		Min.Bending (mm)	
(mm)	(mm)	(kgV/km)						
3.0x5.0	2.0	34	1000	300	1000	500	30%	10 D
4.0x7.0	2.8	42	1000	300	1000	500	30%	10 D

- 1.



**Brand new material**

- > Smooth
- > Anti-UV
- > Long-life

**High Quality Fiber**

- > Fast
- > Long and stability transmission
- > Low Attenuation.



**High Quality PBT Loose Tube Material**

- > Anti-aging
- > Good Protection

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



## APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

### Packaging & Shipping

## PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.