

標準: IEC60277/NZS 5000.2

標準:

標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 rohs 標準符合 IEC60277/NZS 5000.2

標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2

標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2

標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 (標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2: info@himakecable.com)

標準 標準	標準	標準 av 標準	Max標準-20 標準 (Ω 標準)		標準 70
(mm ²)	(mm)	(mm)	標準	標準	(mΩ•km)
2 × 0.5	PVC/0.6	2.7 × 05.3	39	40.1	0.016
2 × 0.75	PVC/0.8	2.9 × 05.7	26	26.7	0.014
2 × 1.0	PVC/0.8	3.1 × 06.1	20	20	0.012

標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2

1. 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2 標準符合 IEC60277/NZS 5000.2





□□□□□□



3. 10 60 internationally





