

产品概述

额定电压 **300/500 V**

额定电压: 300/300V/300/500V

符合 IEC60228/VDE0295 5类K类

导体截面: 0.5-16mm

护套材料: PVC/LSZH/PUR

应用: 工业/民用

护套材料: PVC/LSZH/PUR/EVA

应用: 工业/民用

工作温度: -50-90°C 存储温度: -40-90 °C

弯曲半径: 100 倍导体直径

认证: YY/KVVR/LiYY/RVV

符合 IEC60277/BS6500/VDE0250/GB/T 9330

规格表:

详细规格请参考产品手册

应用:

适用于工业、民用、汽车等行业

联系我们: (info@himake.com)

导体截面 mm ²	芯数	绝缘层厚度-Ø	护套厚度 mm	重量 (kg/km)	重量 (kg/km)
2×0.75	5	0.21	5.6	14.4	39
3×0.75	5	0.21	5.9	21.6	47
4×0.75	5	0.21	6.4	28.8	57
5×0.75	5	0.21	7	36	68
7×0.75	5	0.21	7.6	50.4	87
10×0.75	5	0.21	9.6	72	119
12×0.75	5	0.21	10.3	86.4	145
18×0.75	5	0.21	12	129.6	206

备注:

1. □□□





□□□□□□



3. 15 international 60





