



450 / 750V

2

0.75 4.0

2C 4C 2C + E

X-HF-110

2C ; 4C ; 2C + E

HFS-110-TP

110°C

100 / 500

HF-110

AS / NZS 5000.2 AS / NZS 3013 - WS52W

UV RoHS

info@himakecable.com

mm <sup>2</sup>		mm		mm	O.D. mm
2x0.75	OFC	0.7	TC	1.2	9.5
2x1.5	OFC	0.7	TC	1.2	9.9
4x1.5	OFC	0.7	TC	1.2	11.7
2x0.75 + E	OFC	0.7	TC	1.2	9.8
2x1.5 + E	OFC	0.7	TC	1.2	10.2
4x1.5 + E	OFC	0.7	TC	1.8	13.0











□□□□□





# Quality Comparison

## Purity of copper



**Excellent** 99.93% Oxygen Free Copper ,  
Bright color with long life time .



**Inferior** Copper including a lot of impurity  
Easy heat, short life Easily cause fire

## Flame Test



**Excellent** No spread , and release a little  
white smoke



**Inferior** Keep burning , and pop a lot of black  
HCL toxic smoke

## Resistance Test



**Excellent** low resistivity, high conductivity



**Inferior** High resistivity, High consumption .  
Easy to burning .

## Eccentricity Ratio



**Excellent** Insulation thickness uniformity



**Inferior** Insulation thickness nonuniform  
Easy electric leakage fire disaster,

## High Pressure Test



**Excellent** Jacket no any damage



**Inferior** Jacket damaged , reveal conductor

## High Temperature Test



**Excellent** Jacket no any damage




**Inferior** Jacket damaged , reveal conductor

## Low Temperature Test



**Excellent** Jacket no any damage



**Inferior** Jacket damaged , reveal conductor

3. 10 60 international ly SAA









5. 5월 10일 어린이날을 맞아 어린이들에게 사랑과 관심을 표현하기 위하여 어린이날을 맞아 어린이들에게 사랑과 관심을 표현하기 위하여



