



www.himakecable.com
info@himakecable.com

产品型号 **CY-JZ CY-OZ PVC LiYCY** 产品规格

电压: 300/500V

符合 标准

导体截面: 0.50~6.0mm²

温度: 2°C~61°C

护套 PVC/PVC

长度: 1000mm/100m 1m

符合 标准

护套 PVC/PVC

材料: 聚氯乙烯

温度: 70°C~90°C

厚度 100 规格

规格: CY-JZ-LiYCY

符合 IEC60277BS6500VDE0285 DIN EN50525

性能:

符合 EMCRoHS

EMC 性能

规格:

PVC 规格

联系: info@himake

规格 x 厚度 mm2	厚度 mm	重量 kg/km	重量 kg/km
2x0.5	5.7	35.0	45.0
3G0.5	6.0	42.0	55.0
4G0.5	6.5	47.0	61.0
5G0.5	6.9	56.0	74.0
6G0.5	7.6	67.0	89.0
7G0.5	7.6	69.0	98.0
2x0.75	6.2	40.0	59.0
3G0.75	6.6	52.0	66.0
4G0.75	7.1	60.0	77.0
5G0.75	7.8	71.0	93.0
6G0.75	8.4	80.8	113.0
7G0.75	8.4	91.0	130.0
2x1.0	6.5	50.0	65.0
3G1.0	6.9	60.0	80.0
4G1.0	7.6	71.0	98.0



2. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 22. 23. 24. 25. 26. 27. 28. 29. 30. 31. 32. 33. 34. 35. 36. 37. 38. 39. 40. 41. 42. 43. 44. 45. 46. 47. 48. 49. 50. 51. 52. 53. 54. 55. 56. 57. 58. 59. 60. 61. 62. 63. 64. 65. 66. 67. 68. 69. 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.

1000



□□□□□□□□



3. 15 60 international







[illegible]

