



類別:

型號:

規格: 0.32 mm, 0.4 mm, 0.5 mm, 0.6 mm, 0.7 mm, 0.9 mm

材料: hdpe

長度: 5 至 1600 公尺 100 公尺 6 公尺 1% 公差

重量: 每米 10 克

顏色: 多種選擇

直徑: 0.05 mm 公差

用途: 多種用途

材料: ldpe

長度: 多種選擇

規格: 1 至 100 公尺 100 公尺 500 公尺 公差

材料: hyat

規格: 322 iec 708-1 pe-22

類別:

規格: 150khz 2048Kbits/s 2048Kbits/s

用途: 多種用途

類別: (類別. 用途: info@himakecable.com)

Conductor diameter mm	0.32	0.40	0.50	0.60	0.70	0.90
Max. DC resistance $\Omega$ /km 20 $^{\circ}$ C	236.0	148.0	95.0	65.8	48.0	29.5
Max. Av. DC resistance unbalance% 20 $^{\circ}$ C	2.5	1.5	1.5	1.5	1.5	1.5
Max. DC resistance unbalance% 20 $^{\circ}$ C	6.0	5.0	5.0	5.0	5.0	4.0
Max. pairs to pairs capacitance Unbalance pF/km	250	250	250	200	200	200
Max. Av. pairs to ground capacitance Unbalance pF/km	570	570	570	490	490	490
Max. pairs to ground capacitance Unbalance pF/km				2630		
Max. Av. intrinsic attenuation 150kHz 20 $^{\circ}$ C dB/km	16.0	11.7	8.2	6.7	5.7	4.4
Max. Av. intrinsic attenuation 1024kHz 20 $^{\circ}$ C dB/km	31.1	23.6	18.6	15.8	13.5	10.4
Screen Al-tape continuity	Continuous					
Conductor wire <u>break</u> ing and mixing	No breaking and mixing					

 海迈电缆  
Himake Cable



[www.himakecable.com](http://www.himakecable.com)  
[info@himakecable.com](mailto:info@himakecable.com)

