

□□□□□:



□□□□: 450/750 V□0.6/1 KV

□□: 1 □□□□□□□□ 2 □□□□□□□□□□ 5 □□□□□□ □□□□□□□□□□□□

□□□□□□□: 0.75 ~ 10sqmm

□□□: LSZH□PE LSOH

规格: 5 芯 5 芯 5 芯

材料: LSZH/PE LSOH

规格: 100 m

Max 90, 110, 125°C, 150

规格: 100 m

规格: KYJYJWDZ KYJYJWDZ KYJYJR

规格: IEC60277 BS6500 VDE0250 IEC60332 GB/T9330

规格:

规格: rohs

规格:

规格:

规格 (450/750 v):

(info@himakecable.com)

规格 (mm 2)	规格 (mm)	规格 (mm)	规格 (mm)	规格 (kg/km)	Max-20 (Ω)	规格 70 (mΩ•km)
2x0.75	PVC/0.6	PVC/1.2	7.5	67.72	24.5	0.012
2x1.0	PVC/0.6	PVC/1.2	7.82	76.2	18.1	0.011
2x1.5	PVC/0.7	PVC/1.2	8.74	97.71	12.1	0.011
2x2.5	PVC/0.8	PVC/1.2	9.96	133.4	7.41	0.01
2 x 4	PVC/0.8	PVC/1.2	10.9	173.65	4.61	0.0085

规格:

1.



[illegible]

11



□□□□□□□



3. 10 60 internationally









_____ "_____".

