

□□□□□:

海迈电缆  
Himake Cable

聚氯乙烯绝缘  
PVC Insulation

铜芯导体  
Copper conductor

www.himakecable.com  
info@himakecable.com

CCC CE SAA UL CB R&HS

□□□□: 300/300 V

□□: □□ 5 □□□□□□□□

□□□□□□: 0.3 □ 2.5sqmm

□□□: LSZH□LSOH

□□□□□: □ + □□□□ + □□□□□ + □□□ □□□□□□□□ +

Max□□□□□□ 90, 110, 125°C, 150

□□□□□: 100 □□□□□□□□□□□□

□□□□□□□: WDZ RYJS□H03Z □□H05Z □

Standards: IEC60277 BS6500 VDE0281 GB/T IEC60332 5023

**Product Name:**

Product description and RoHS compliance information.

**Technical Specifications:**

Additional technical details or notes.

**Contact Information:** (Email: [info@himakecable.com](mailto:info@himakecable.com))

Cable Size (mm)	Max. Diameter (mm)	Weight (kg/km)	Max. Voltage -20 (Ω km)	Resistance 70 (mΩ·km)	Current (A)
2 × 0.3	4.3	13.4	69.2	0.016	7.4
2 × 0.4	4.6	17	48.2	0.014	9.0
2 × 0.5	6.0	24	39.0	0.014	10
2 × 0.75	6.2	31	26.0	0.014	13
2 × 1.0	6.6	34	19.5	0.011	16
2 × 1.5	7.2	45	13.3	0.010	20
2 × 2.5	8.2	65	7.98	0.009	27

**Notes:**

1. Additional note or disclaimer.









□□□□□□







3. 10 60 internationally















