



Max 90, 110, 125°C, 150

Length: 100 m

Model: KYJYJ22-WDZ KYJYJ22

Standards: IEC60277 BS6500 VDE0250 GB/T9330 IEC60332

**Features:**

RoHS compliant

**Applications:**

General purpose

**Specifications (450/750 v):**

Contact: info@himakecable.com

| Cable Size (mm <sup>2</sup> ) | Conductor (mm) |          | Insulation (mm) |          | Overall (mm) |          | Weight (kg/km) |          |
|-------------------------------|----------------|----------|-----------------|----------|--------------|----------|----------------|----------|
|                               | 450/750 V      | 0.6/1 KV | 450/750 V       | 0.6/1 KV | 450/750 V    | 0.6/1 KV | 450/750 V      | 0.6/1 KV |
| 2 x 4                         | PVC/0.8        | PVC/1.0  | PVC/1.5         | PVC/1.8  | 16.9         | 18.3     | 656            | 725      |
| 2 x 6                         | PVC/0.8        | PVC/1.0  | PVC/1.5         | PVC/1.8  | 17.9         | 19.3     | 744            | 816      |
| 2 x 10                        | PVC/1.0        | PVC/1.0  | PVC/1.7         | PVC/1.8  | 21.7         | 21.9     | 1019           | 1028     |
| 3 x 2.5                       | PVC/0.8        | PVC/0.8  | PVC/1.5         | PVC/1.8  | 16.5         | 17.1     | 634            | 657      |
| 3 x 4                         | PVC/0.8        | PVC/1.0  | PVC/1.5         | PVC/1.8  | 17.5         | 19       | 727            | 803      |

**Notes:**

1. General purpose







□□□□□□



3. 10 60 internationally













