

□□□□□:



□□□□: 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□: □□□ 2 □□□□□□□□□□□□□□□□

□□□□□□□: 25 □ 1000sqmm

□□□: □□□□□□□□

□□□□□: □□□□□□□□□□□□

□□□□: □□□□□□□□□□□□ + □□□□□□ + □□□□□□□□

□: □□□□□□□□□ PVC Rohs □□□□

□□□□□: □□□□□□□□□□

Max□□□□□□□ 90

□□□□□: □□□□□□□□□□□□

YJLV YJLV62 YJLV72

IEC60502 BS6622 VDE0276 GB/T12706 IEC60332

RoHS

RoHS

Technical Specifications

26/35

Contact: info@himakecable.com

Conductor Cross-section (mm ²)	XLPE Insulation (mm)	Cable Diameter (mm)	Rated Current (A)	Weight (Kg/Km)
50	4.5	24.2	245	952
70	4.5	26.1	305	1190
95	4.5	27.7	370	1461
120	4.5	29.3	430	1738
150	4.5	30.9	490	2054
185	4.5	32.7	560	2427
240	4.5	35.1	665	3001
300	4.5	37.3	765	3604
3 x 50	4.5	51	178	3265
3 x 70	4.5	54.8	246	4014
3 x 95	4.5	58.5	267	4898
3 x 120	4.5	61.7	308	5767
3 x 150	4.5	65.3	335	6833
3 x 185	4.5	69	394	8040
3 x 240	4.5	74.1	465	9945
3 x 300	4.5	79.1	528	11863

Notes

1. ...



□□□□□□



3. 10 60 internationally





