

□□□□:

海迈电缆
Himake Cable

Info@himakecable.com

CCC CE SAA UL CB R6HS

www.himakecable.com
info@himakecable.com

□□□□: 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□: □□ 2 □□□□□□□□□□□□□□□□□□

□□□□□□: 25 □ 1000sqmm

□□□: □□□□□□□□

□□□□□: □□□□□□□□□□□□

□□□□: □□□□□□□□□□□□ + □□□□□□ + □□□□□□□□

□□: □□□□□□□□□□ PVC Rohs □□□□

□□□□□□: □□□□□□□□□□

Max 90

Material: Polyethylene

Model: YJV/YJV62/YJV72

Standards: IEC60502/BS6622/VDE0276 GB/T12706 IEC60332

Features:

Low smoke and halogen free (LSHF) cable, complies with RoHS

Applications:

Used for power transmission and distribution in industrial and commercial buildings

Contact Information: (Email: info@himakecable.com)

Cable Size (mm ²)	XLPE Insulation (mm)	Overall Diameter (mm)	Rated Current (A)	Weight (Kg/Km)
50	4.5	24.2	245	952
70	4.5	26.1	305	1190
95	4.5	27.7	370	1461
120	4.5	29.3	430	1738
150	4.5	30.9	490	2054
185	4.5	32.7	560	2427
240	4.5	35.1	665	3001
300	4.5	37.3	765	3604
3 x 50	4.5	51	178	3265
3 x 70	4.5	54.8	246	4014
3 x 95	4.5	58.5	267	4898
3 x 120	4.5	61.7	308	5767
3 x 150	4.5	65.3	335	6833
3 x 185	4.5	69	394	8040
3 x 240	4.5	74.1	465	9945
3 x 300	4.5	79.1	528	11863

Notes:

1. Cable length is standard 1000m





□□□□□□



3. 10 60 internationally





