

□□□□□:



□□□□: 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□: □□ 2 □□□□□□□□□□□□□□□□□□

□□□□□□□: 25 □ 1000sqmm

□□□: □□□□□□□□

□□□□□: 1 C: □□□□3 C: □ + □ + □□ □□□□□□□□

□□□□: □□□□□□□□□□□□ + □□□□□□ + □□□□□□□□

□□□□□: □□□□□□□□

□: □□□□□□□□ PVC Rohs □□□□

□□□□□: □□□□□□□□□□

**Max**□□□□□□ 90

□□□□□: □□□□□□□□□□□□

□□□□□□□: YJV22□ZR YJV22

規格: IEC60502 BS6622 VDE0276 GB/T12706 IEC60332

**產品名稱:**

此產品符合歐盟RoHS指令，不含鉛、汞、鎘、六價鉻、多環芳烴及多溴聯苯等有害物質。

**產品規格:**

此產品符合IEC 26/35標準，適用於室內及室外敷設，具有優良的電氣性能及機械性能。

**查詢及訂購:** (電子郵件: info@himakecable.com)

規格 (mm <sup>2</sup> )	XLPE 厚度 (mm)	總寬度 (mm)	額定電流 (A)	重量 (A)	重量 (Kg/Km)
3 x 25	4.5	50.6	126	154	3358
3 x 35	4.5	53	151	184	3816
3 x 50	4.5	56.2	181	218	4494
3 x 70	4.5	60	225	267	5333
3 x 95	4.5	64.1	273	318	6359
3 x 120	4.5	67.5	311	360	7338
3 x 150	4.5	71.1	353	404	8493
3 x 185	4.5	75	402	456	9824
3 x 240	4.5	80.3	473	531	11894
3 x 300	4.5	86.9	540	598	14826

**備註:**

1. 此產品為標準規格，如有特殊要求，請洽詢本公司。







□□□□□□



3. 10 60 internationally











