

□□□□□:



□□□□: 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□: □□ 2 □□□□□□□□□□□□□□□□□□

□□□□□□: 25 □ 1000sqmm

□□□: □□□□□□□□

□□□□□: 1 C: □□□□3 C: □ + □ + □□ □□□□□□□□

□□□□: □□□□□□□□□□□□ + □□□□□□ + □□□□□□□□

□□□□□: □□□□

□□: □□□□□□□□ PVC Rohs □□□□

□□□□□: □□□□□□□□□□

Max□□□□□□ 90

□□□□□: □□□□□□□□□□□□

□□□□□□□: YJV32□ZR YJV32

規格: IEC60502 BS6622 VDE0276 GB/T12706 IEC60332

產品名稱:

此產品符合歐盟RoHS指令，不含鉛、汞、鎘、六價鉻、多環芳烴、多溴聯苯、多溴聯苯醚等有害物質。

產品規格:

此產品符合IEC60502、BS6622、VDE0276、GB/T12706、IEC60332等國際標準。產品採用XLPE絕緣材料，具有優良的電氣性能和機械性能。

聯繫方式: (電子郵件: info@himakecable.com)

規格 (mm ²)	XLPE 絕緣 (mm)	總直徑 (mm)	額定電流 (A)	重量 (Kg/Km)
3 x 25	4.5	53.8	128	4821
3 x 35	4.5	56.2	155	5366
3 x 50	4.5	59.4	185	6156
3 x 70	4.5	63.2	230	7096
3 x 95	4.5	67.3	276	8265
3 x 120	4.5	70.7	316	9312
3 x 150	4.5	75.6	358	11445
3 x 185	4.5	79.5	409	12910
3 x 240	4.5	84.8	482	15220
3 x 300	4.5	90.2	546	17581
3 x 400	4.5	100.2	647	21722

備註:

1. 此產品為標準規格，如有特殊要求，請洽詢銷售人員。





□□□□□□



3. 10 60 internationally





