

□□□□:

海迈电缆  
Himake Cable



himakecable



www.himakecable.com  
info@himakecable.com

□□□□:18/30 KV 21/35 KV 26/35 KV

□□: □□ 2 □□□□□□□□□□□□□□□□□□

□□□□□□: 25 □ 1000sqmm

□□□: □□□□□□□□

□□□□□: □□□□□□□□□□□□

□□□□: □□□□□□□□□□□□ + □□□□□□ + □□□□□□□□

□□: □□□□□□□□□□ PVC Rohs □□□□

□□□□□□: □□□□□□□□□□

Max 90

Material: PVC

Model: YJV/YJV62/YJV72

Standards: IEC60502, BS6622, VDE0276, GB/T12706, IEC60332

Features:

RoHS Compliant

Applications:

26/35

Contact: info@himakecable.com

Conductor Area (mm <sup>2</sup> )	XLPE Insulation (mm)	Cable Diameter (mm)	Rated Current (A)	Weight (Kg/Km)
50	9.3	35.8	245	1551
70	9.3	37.5	305	1792
95	9.3	39.5	370	2127
120	9.3	40.7	425	2415
150	9.3	42.5	485	2778
185	9.3	44.1	555	3164
240	9.3	46.5	650	3764
300	9.3	48.9	745	3782
400	9.3	52.3	870	4444
500	9.3	57.7	1000	5518
630	9.3	61.6	1160	5926

Notes:

1. Cable length is standard 1000m.



2 下列各句，没有语病的一句是

□□□□



□□□□□□



3. 10 60 internationally











