



3 300/500V 450/750V TPS

300/500V 450/750V

CCA

0.75 16mm

2C 2CE

PVC PVC PE LSZH LSHF

3C: 2C E: E

PVC PVC LSZH LSHF

70°C 90°C

100

BVVB H05VVH2-U H07VVH2-R BS6004 624*Y TPS

IEC60277 BS6004 VDE0281 GB/T 5023

RoHS:

RoHS

RoHS:

RoHS: (info@himake)

Area (mm ²)	Count	Material (mm)	Material (mm)	Dimensions (mm)	Weight (g)
3×1.0	1	PVC/0.6	PVC/0.9	4.8×8.7	64
3×1.5	1	PVC/0.7	PVC/0.9	5.3×11.1	91.6
3×1.5	2	PVC/0.7	PVC/0.9	5.4×11.4	97
3×2.5	2	PVC/0.8	PVC/1.0	6.2×13.8	132
2×1.01.0(E)	1	PVC/0.6	PVC/0.9	4.7×8.6	62
2×1.51.0(E)	2	PVC/0.7	PVC/0.9	5.4×9.6	87
2×2.51.5(E)	2	PVC/0.8	PVC/1.0	6.2×11.5	120
2×4.01.5(E)	2	PVC/0.8	PVC/1.0	7.2×13.0	170
2×6.02.5(E)	2	PVC/0.8	PVC/1.1	8.0×15.0	240

RoHS:

ADVANTAGE

WHY US?

Source manufacturers direct, non - agent, no price difference



Professional instrument detection,
strict control, adhere to the quality .



Swing test



Tensile strength test



Print friction test



Temperature test



Insulation resistance test



UV test

PACKAGING LOGISTICS



