



- 紧套光纤
Tight buffer fiber
- 芳纶
Aramid yarn
- 子单元护套
Subunit Jacket
- LSZH护套
LSZH Jacket
- 非金属加强芯
FRP strength member



产品特点

1. 传输速率高
2. 传输距离远
3. 2 ~ 144 芯
4. 使用寿命长

应用场合

广泛应用于电信、金融、工业、医疗、教育、科研等领域。

联系我们 (电子邮箱: info@himakecable.com)

规格	外径 Φ	重量 (kg/km)	抗拉强度 (N)		弯曲半径 (NV100 mm)		护套厚度 (mm)	
规格	(mm)	(kg/km)	最小	最大	最小	最大	最小	最大
12	15.5	205	1500	500	1500	600	20 D	10 D
24	15.5	205	1500	500	1500	600	20 D	10 D
36	17.5	255	1500	500	1500	600	20 D	10 D
48	17.5	255	1500	500	1500	600	20 D	10 D
60	19.5	320	1500	500	1500	600	20 D	10 D
72	19.5	320	1500	500	1500	600	20 D	10 D
96	22	395	1500	500	1500	600	20 D	10 D
144	28	597	1500	500	1500	600	20 D	10 D

产品特点

1. 本产品采用最新材料，具有光滑、抗UV、长寿命等特点。



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.